



WITH CONICAL CLAMPING BUSHING

200 - 5,000 Nm



PROPERTIES

MATERIAL


Hardened steel (nitrocarburized surface)

DESIGN

► Drive side: coupling hub with conical clamping bushing connection (spline profile on request)

► Driven side: output flange with 12x fastening threads and integral bearings

► Safety elements: evenly spaced around the circumference; externally adjustable



MODEL STN | SIZE 2 - 5

SIZE		2			5		
Adjustment range available from - to		0.2-0.5	0.5-1.0	1.0-1.5	0.7-2	1.2-4	3.2-5
		3×ST10	6×ST10	6×ST10	3×ST15	6×ST15	6×ST15
Overall length	(mm) A ₁		124.5			160	
Flange outside diameter	(mm) B		198			220	
Fit length / keyway length	(mm) C ₁		118			155	
Effective clamping length	(mm) C ₂		45			82	
Bore diameter possible Ø to Ø F7	(mm) D ₁		45-70			40-80	
Bore diameter max. Ø F7 with keyway	(mm) D ₁		60			70	
Inside diameter	(mm) E		132			145	
Flange centering diameter H7	(mm) F		162			170	
Bolt circle diameter ±0.3	(mm) G		192			209	
Outside diameter h7	(mm) H		12×M10			12×M12	
Thread depth	(mm) I		15			20	
Fit length	(mm) J		3			4	
Tightening screw ISO 4017			6×M10			6×M10	
Tightening torque	(Nm) K		59			59	
Distance	(mm) L		18			26.5	
Distance	(mm) M		56			76.5	
Actuation path	(mm) N		3.5			4.5	
Mounting diameter - elements	(mm) O		154			170	
Hub outside diameter	(mm) P		119			136	
Moment of inertia (approx.) D max. + max. sgmnt	(10 ⁻³ kgm ²)		77			151	
Speed max.	(rpm)		7000			6000	
Allowable max. radial force standard*	(KN)		5			10	
Approx. weight at D max. + max. sgmnt	(kg)		15			24	

* larger radial loads possible with special bearings

STN

WITH CONICAL CLAMPING RING

2,000 - 165,000 Nm



PROPERTIES

MATERIAL


Hardened steel (nitrocarburized surface)

► Driven side: output flange with 12x fastening threads and integral bearings

DESIGN

► Drive side: coupling hub with conical clamping ring connection (spline profile on request)

► Safety elements: evenly spaced around the circumference; externally adjustable



SAFETY COUPLINGS
ST

MODEL STN | SIZE 10 - 160

SIZE	10			25			40			60			160		
Adjustment range available from - to (KNm)	2-5	4-10	6-14	6-12	9-18	15-25	12-21	22-32	32-45	11-18	22-36	30-55	25-55	50-110	80-165
	3xST15	6xST15	6xST15	6xST15	9xST15	12xST15	6xST30	6xST30	9xST30	3xST30	6xST30	9xST30	3xST70	6xST70	9xST70
Overall length (mm)	A ₁	210			227			286			318			425	
Flange outside diameter (mm)	B	270			318			428			459			648	
Fit length / keyway length (mm)	C ₁	147			152			191			218			305	
Effective clamping length (mm)	C ₂	62			67			93.5			93			125	
Bore diameter possible Ø to Ø F7 (mm)	D ₁	65-110			70-150			110-170			80-200			140-290	
Bore diameter max. Ø F7 with keyway (mm)	D ₁	100			140			160			180			270	
Inside diameter (mm)	E	170			210			270			300			450	
Flange centering diameter H7 (mm)	F	220			260			330			360			570	
Bolt circle diameter ±0.3 (mm)	G	259			298			380			418			618	
Outside diameter h7 (mm)	H	12xM16			12xM16			12xM20			12xM20			12xM24	
Thread depth (mm)	I	25			30			36			35			40	
Fit length (mm)	J	6			8			9			8			11	
Tightening screw ISO 4017	K	8xM16			9xM16			11xM16			8xM20			8xM24	
Tightening torque (Nm)		180			180			180			570			710	
Distance (mm)	L	72			80			82.5			94			151	
Distance (mm)	M	122			127			151			163			240	
Actuation path (mm)	N	4			4			8			7.5			10	
Mounting diameter - elements (mm)	O	220			270			350			376			532	
Hub outside diameter (mm)	P	218			278			322			378			535	
Moment of inertia (approx.) D max. + max. sgmnt (10 ⁻³ kgm ²)		446			789			3570			5700			30700	
Speed max. (rpm)		4200			3800			3000			2500			2000	
Allowable max. radial force standard* (KN)		20			30			40			50			100	
Approx. weight at D max. + max. sgmnt (kg)		50			65			166			200			550	

* larger radial loads possible with special bearings